


# AQS-400 / Mono

The AQS-400 Neon Flex product is manufactured in a continuous extrusion process and then manually terminated to length with IP65 overmolded cable entry points here in our Sydney factory for a quicker turn-around time.

# AQS-400-MONO

## Neon Flex



Product	AQS-400-Mono
Voltage	24V DC
Watts (per Meter)	05W / 10W
IP Rating	IP65
Lumen Output (per Meter)	500lm to 620lm
CCT & Colour Options	2700K / 3000K / 4000K / 5000K
Working Mode	Constant Voltage (PWM) / DMX / DALI
Max Length (Single Power Feed)	10m / 6m
Max Length (Double Power Feed)	20m / 12m
Cut Interval	31mm
Bend Direction	Vertically
Minimum Bend Diameter	60mm
LED Type	2216
LED Qty / M	192pcs
Lumen Maintenance	70,000 Hours L70@ 25°C, 50,000 Hours L70@ 50°C
Materials	Silicone
Emission Angle	180°
Operating Temperature	-20° to +40°C
Installation Temperature	5° to +35°C
Warranty	3 Year Aqualux Warranty

### Example Product Code Variation

Produce Code	Size	CCT	Voltage	W / M	Lm/M
AQS-400-20A10	0910	2000K	24V DC	10W	400lm
AQS-400-27A05	0910	2700K	24V DC	5W	260lm
AQS-400-27A10	0910	2700K	24V DC	10W	500lm
AQS-400-30A05	0910	3000K	24V DC	5W	270lm
AQS-400-30A10	0910	3000K	24V DC	10W	530lm
AQS-400-40A10	0910	4000K	24V DC	10W	540lm
AQS-400-50A10	0910	5000K	24V DC	10W	545lm

### Dimming Options

PSU Control (1-10V / PWM / Phase / Remote)  
24V Control (PWM)


For wiring diagrams please refer to the aqualux website: [www.aqualux.com.au](http://www.aqualux.com.au)  
/ Support / Downloads / Wiring Diagrams

# Neon Flex

## Variations

Product Code	CCT Kelvin	Voltage Direct Current	Watts Meter	Lumens Meter	Max Run Single End	Max Run Double End
AQS-400-20A10	2000K	24V DC	10W	400lm	6m	12m
AQS-400-27A05	2700K	24V DC	5W	260lm	10m	20m
AQS-400-30A05	3000K	24V DC	5W	270lm	10m	20m
AQS-400-27A10	2700K	24V DC	10W	500lm	6m	12m
AQS-400-30A10	3000K	24V DC	10W	530lm	6m	12m
AQS-400-40A10	4000K	24V DC	10W	540lm	6m	12m
AQS-400-50A10	5000K	24V DC	10W	545lm	6m	12m

### Bending Directions




# Neon Flex


## Mounting

AQS-400-ACC-03  
1m Polycarbonate

AQS-400-ACC-04  
2m Polycarbonate




AQS-400-ACC-01  
Aluminium clip




### Direct Cable Entry

D01




### Direct Cable Entry



### Silicone End Caps

The use of glues and resins as fixing agents should be avoided. If the use of a glue or adhesive compound cannot be avoided, a neutral pH silicone-based compound is suggested.

High VOC, Epoxy-based resins, cyanoacrylate or other adhesives will void the warranty.



## Neon Flex

### AQS Family Reference Table

Product	Type	IP Rating	LED Options	Size mm	Power/m	Application
AQS-170	Cob Strip	IP20	Mono	10mm	10W DC	Internal / Profile required
AQS-172	Cob Strip	IP20	Mono	4mm	5W DC	Internal / Profile required
AQS-180	HE Strip	IP20	Mono	10mm	20W DC	Internal / Profile required
AQS-400	Neon Flex	IP65	Mono	10 x 9	5W DC / 10W DC	External / No profile required
AQS-401	Neon Flex	IP65	Mono	10 x 10	10W DC	External / No profile required
AQS-402	Neon Flex	IP67	Mono	6 x 12	10W DC	External / No profile required
AQS-410	Neon Flex	IP65	RGB	13 x 12	10W DC	External / No profile required
AQS-420	Neon Flex	IP65	Mono / RGBW	12 x 20	10W / 15W	External / No profile required
AQS-500	Neon Flex	IP68	Mono / RGB / RGBW / DMX	11.5 x 21	5W / 8W / 12W / 18W	External / Submerged / No profile
AQS-505	Neon Flex	IP68	Mono	13.5 x 13.5	10W	External / Submerged / No profile
AQS-510	Neon Flex	IP68	Mono / RGB / RGBW / DMX	16.5 x 16.5	10W / 13W / 17W / 18W	External / Submerged / No profile

### Extension Wire Recommendations

Maximum extension wire length according to light power

Watts	22AWG 0.34mm <sup>2</sup>	20AWG 0.53mm <sup>2</sup>	18AWG 0.82mm <sup>2</sup>	17AWG 1.04mm <sup>2</sup>	16AWG 1.38mm <sup>2</sup>	14AWG 2.07mm <sup>2</sup>	12AWG 3.29mm <sup>2</sup>	10AWG 5.62mm <sup>2</sup>
10W	36m	60m	100m	120m	140m	240m	400m	600m
20W	18m	30m	50m	60m	70m	120m	200m	300m
30W	12m	20m	30m	38m	45m	80m	130m	200m
40W	8m	15m	22m	28m	35m	60m	95m	140m
50W	6m	12m	18m	22m	28m	48m	75m	105m
60W	5m	10m	15m	18m	22m	36m	60m	88m
70W	-	8m	12m	14m	18m	30m	50m	72m
80W	-	6m	10m	11m	14m	24m	40m	58m
90W	-	4m	7m	8m	10m	18m	30m	45m
100W	-	-	5m	6m	7m	12m	22m	32m
110W	-	-	3m	4m	5m	8m	15m	22m
120W	-	-	2m	2.5m	3m	0m	8m	12m