

Creating the Legend

The new Aqualux 'AQL' product code is created from key detailed elements directly related to your chosen fitting.

Structured to quickly give you all the relevant information you need, at a glance.

AQL-XXX-AA-BCCCDDEEF

AA	Material	Finish
A0	Aluminium	Custom
A1	Aluminium	Satin Chrome
A2	Aluminium	Black
A3	Aluminium	Aged Brass
A4	Aluminium	Gunmetal Grey
A8	Aluminium	White
B0	Brass	Custom
B1	Brass	Brushed Chrome
B2	Brass	Black
B3	Brass	Aged Brass
B4	Brass	Gunmetal Grey
B5	Brass	Copper
B6	Brass	Natural Brass
B7	Brass	Bronze
C0	Copper	Custom
C1	Copper	Natural Copper
C2	Copper	Black
S0	Stainless 316/304	Custom
S1	Stainless 316	Natural
S2	Stainless 304	Natural
S3	Stainless 316	Black

CCC	Watts
001	1W
002	2W
003	3W
004	4W
006	6W
007	7W
008	8W
009	9W
010	10W
021	21W
050	50W
100	100W
200	200W
300	300W
400	400W
500	500W
600	600W
800	800W
1000	1000W

Note: Not all fittings come with every variant displayed here, please check the Aqualux website for product variations

DD	White CCT
22	2200K
25	2500K
27	2700K
30	3000K
35	3500K
40	4000K
45	4500K
50	5000K
57	5700K
60	6000K
65	6500K

DD	Colour / Multi
RD	Red
GN	Green
BU	Blue
PK	Pink
AM	Amber
OR	Orange
LY	Lemon Yellow
Z0	Custom
Z1	RGB
Z2	RGBW (3000K)
Z3	RGBW (2700K)
Z4	RGBW (6500K)
Z5	DMX RGB
Z6	DMX RGBW (2700K)
Z7	RGBA (Amber)

F	Cable / Termination Style
S	Standard (Varies by Product)
Q	AqualuxPLUS QuickConnect
T	Terminal Block

EE	Beam ° FWHM / Distribution
10	10° FWHM
15	15° FWHM
20	20° FWHM
25	25° FWHM
30	30° FWHM
35	35° FWHM
36	36° FWHM
38	38° FWHM
40	40° FWHM
50	50° FWHM
60	60° FWHM
70	70° FWHM
DF	Diffuse Frosted
DC	Diffuse Clear
A1	Asymmetric / Cutoff
A2	Asymmetric / Billie Lens
A3	Wall Wash
O1	Oval 25x50°

B	Input Voltage	Dimming	Conductors	Polarity
X	12-24V AC / 24V DC	Non Dimming	2 (Power)	No
D	24V AC	TRIAC / Phase Cut Dimming	2 (Power)	No
C	Constant Current	Gontrol Geart Dependant (DALI/DMX/1-10/PWM)	2 (Power)	Yes
Z	24V DC	4CH PWM Dimming, Common Anode	6 (2 Power / 4 Signal PWM)	Yes
E	24V DC	PWM Dimming	2/4/5 (Power PWM)	Yes
B	24V DC	PWM Dimming, 3-Wire PWM DRV	3 (2 Power / 1 Signal PWM)	Yes
L	24V DC	DALI Dimming, Integral	4 (2 Power / 2 DALI)	Yes
M	MR16	Lamp Dependant	2 (Power)	No
G	GU10	Lamp Dependant	2 (2 Power)	No
F	240V AC	Control Gear Dependant	3 (2 Power / 1 Earth)	No
H	24V AC / DC	PWM Dimming	2 (Power PWM)	No
J	12V DC	PWM Dimming	2 (Power)	No
K	24V DC	Non Dimming	2 (Power)	Yes