aqualux
LIGHTING

SPIKE
Feature Guide

NEW

QUICK GUIDE	HYDRA - AQL-455	HYDRA - AQL-450	HYDRA - AQL-400	PHOENIX - AQL-503	LUMENA - AQL-115
	NEW versatile entry level fitting with latest LED technology.	Mid level fitting with multi-colour output options and optics.	Mid level fitting with multi-colour output options, finishes and optics.	High end fitting with multi-colour output, RGBW options, finishes and optics.	High end fitting with multi-colour, RGBW output options, finishes and optics.
Price	$'s	$$'s	$$'s	$$$'s	$$$'s
Light Source	Integrated CREE	MR16 (included)[1]	MR16	MR16 / Intergrated	Integrated CREE
Lumens	500lms	250lms	250lms / 550lms	250lms / 300lms / 550lms	300lms / 550lms
Power	6.5W	4W	4W / 6W	(MR16) 4W / 6W / (Integrated) 7W	4W / 7W
Finishes	Matt Black	Matt Black	Aged Brass	Natural Brass	Silver Anodised
	—	Brushed Chrome	Brushed Chrome	Matt Black	Black Anodised
	—	—	—	Brushed Chrome	Bronze Anodised
	—	—	—	Aged Brass	Grey Anodised
Material	CNC Aluminium	Cast Brass	Cast Brass	Cast Brass	CNC Aluminium
Lead time	Stocked	Stocked	Stocked	Stocked/10-14 Days Lead Time	Stocked/10-14 Days Lead Time
Input	1m Double Insulated 0.5mm^2	Twin Core	Twin Core	1m Double Insulated 0.5mm^2	Aqualux M8 / M12 QC connectors
DETAILED SPECIFICATIONS					
CCT					
Red	—	■[2]	■	■	■
Green	—	■[2]	■	■	■
Blue	—	■[2]	■	■	■
Amber	—	■[2]	■	■	■
2700K	—	—	—	■	■
3000K	■	■	■	■ Standard	■ Standard
5700K	—	■[2]	■	■	■
RGBW	—	—	—	■	■
MR16	—	✓	✓	✓[3]	—
WARRANTY					
2 Year	✓	—	✓	—	—
3 Year	—	—	—	—	—
5 Year	—	✓	✓	✓	✓
OPTICAL					
10°	—	✓[2]	✓	✓(MR16[3] and Integrated)	✓
25°	—	—	—	✓(Integrated)	✓
38°	✓	✓	✓	✓(MR16)[3]	—
40°	—	—	—	✓(Integrated)	✓
60°	—	✓[2]	✓	✓(MR16)[3]	—
ACCESSORIES					
Elbow	—	—	✓	—	—
Extension	—	✓ 150mm / 300mm	✓ 150mm / 300mm	✓ 150mm / 300mm	—

1. 4W AGL-250-30X38.
2. Requires purchase of separate globe.
3. Optional.